



Revolutionizing the
Cold Chain

ATA-R36—Refrigerated Container

Ultra-Rugged Design

*** 5 Day Hold Time ***

Kodiak's ATA-36 uses the same technology and components of the R36.

The ATA-R36, 36 liter container offers a breakthrough in the shipment of temperature-critical products. The Kodiak container incorporates patented technologies to maintain an internal temperature of +2°C to +8°C for 5 days at an average ambient temperature of 25°C.

Kodiak's patented Thermal Regulating technology employs a Thermal Switch in the frozen lid to monitor and maintain the temperature within the container. Our patented Thermal Shield protects the cargo area from ambient temperature spikes by allowing heat absorption throughout the entire cargo area.

The ATA-R36 is encased in high-quality, high-tech vacuum insulation technology providing 10 times more insulation capability than standard foam insulated boxes.

The rugged outer-box ensures that you can reuse your Kodiak container over 100 times thus reducing your per-shipment costs.



Features:

- ◇ Vacuum panel insulation technology.
- ◇ Patented Thermal Regulation 2-8°C.
- ◇ Patented Thermal Shield helps protect payload.
- ◇ No external power source required—unit is completely self-contained
- ◇ Full 36 liter useable cargo space.
- ◇ No gel packs or ice required in cargo area.
- ◇ Onboard or drop-in data loggers available.
- ◇ Durable, reusable container protects product and addresses environmental issues—no recycling or disposal necessary
- ◇ Replaceable lids for fast turnaround.
- ◇ Single-handle carry.

Applications:

- ◇ Pharmaceuticals
- ◇ Blood
- ◇ Adhesives
- ◇ Food Products
- ◇ Industrial Chemicals
- ◇ Veterinary Supplies
- ◇ Disaster Recovery Storage

Specifications	
Temperature Range	2° to 8° C (35.6° to 46.4° F)
Hold Time	5 Days Average ambient temperature of 24° C
Payload Capacity	36L (1.4 ft ³)
Cooling Medium	
Intelligent Thermal Regulating Unit	
Interior Dimensions	44.4 x 30.4 x 27.8 cm (17.5 x 12 x 11 in)
Exterior dimensions	63.66 x 53.66 x 53.98 cm (25.1 x 21.13 x 21.25 in)
Weight (Empty)	77 lb (34.93 kg)



Kodiak Thermal Technologies, Inc.

333 N Sam Houston Pkwy E, Ste 400
Houston, TX 77060
PH: (888-340-1110
FX: (713) 682-7699
www.GoKodiak.com
info@GoKodiak.com